

NEWSPRINT Datasheet

Grammage	ISO 536	g/m2	80
Grain direction (source format)	70 x 100		LG
Thickness	ISO 534	µm	90 - 100
Bulk	ISO 534	cm3/g	1,3
Roughness Bendtsen	ISO 8791-2	ml/min	
Smoothness Sheffield	ISO 8791-3	s	
Brightness	ISO 2471 (D65)	%	
Opacity	ISO 2471	%	98
Whiteness	ISO 11475	%	82
Indigo			suitable since lightly pigmented
Additional print processes			Toner, Riso, Offset
Suitable for preprint			oui

Tolerances ±

Grammage	ISO 536	g/m2	2
Thickness	ISO 534	µm	
Bulk	ISO 534	cm3/g	
Roughness Bendtsen	ISO 8791-2	ml/min	
Smoothness Sheffield	ISO 8791-3	s	
Brightness	ISO 2471 (D65)	%	
Opacity	ISO 2471	%	
Whiteness	ISO 11475	%	

GREEN RESPONSIBILITY

FSC Mix: SGSCH-COC-009212
 EU Ecolabel
 63% recycled and 37% virgin fiber
 ECF (elementary chlorine free)
 lifespan class 6-40 (Durability of at least 50 years)